

### Cylinder/Tubes

DIECO Part #	O.D. (in)	I.D. (in)	Length (in)
PXC10	1	1/4	12
PXC15	1 1/2	3/8	12
PXC20	2	5/8	12
PXC25	2 1/2	5/8	12
PXC30	3	3/4	12
PXC40	4	1	12
PXC50	5	1 1/4	12
PXC60	6	1 1/2	12

Other sizes and durometers available



Other O.D.s & I.D.s available  
Durometers: 80A, 90A, 95A

### Closed-End Punch Strippers

DIECO Part #	I.D. (in)	O.D. (in)	Length (in)
PT-018	3/16	11/16	1 1/4, 1 1/2
PT-025	1/4	3/4	1 1/4, 1 1/2, 1 3/4
PT-031	5/16	13/16	1 1/4, 1 1/2, 1 3/4, 2
PT-037	3/8	7/8	1 1/4, 1 1/2, 1 3/4, 2, 2 1/4
PT-050	1/2	1	1 1/4, 1 1/2, 1 3/4, 2, 2 1/4, 2 1/2
PT-062	5/8	1 1/8	1 1/4, 1 1/2, 1 3/4, 2, 2 1/4, 2 1/2
PT-075	3/4	1 1/2	1 3/4, 2, 2 1/4, 2 1/2, 2 3/4
PT-087	7/8	1 3/4	1 3/4, 2, 2 1/4, 2 1/2, 2 3/4
PT-100	1	2	1 3/4, 2, 2 1/4, 2 1/2, 2 3/4
PT-125	1 1/4	2 1/2	2, 2 1/4, 2 1/2, 2 3/4, 3
PT-150	1 1/2	2 3/4	2, 2 1/4, 2 1/2, 2 3/4, 3

Standard Durometer: 95A Red

### Urethane Springs

Punch Body Dia (in)	O.D. Lt. Duty (in)	O.D. Med. Duty (in)	O.D. Heavy Duty (in)	Lengths (in)
3/16	11/16	13/16	15/16	1, 1 1/4, 1 1/2, 12 1/2
1/4	3/4	7/8	1	1, 1 1/4, 1 1/2, 1 3/4, 12 1/2
5/16	11/16	15/16	1 1/16	1, 1 1/4, 1 1/2, 1 3/4, 12 1/2
3/8	7/8	1	1 1/8	1, 1 1/4, 1 1/2, 1 3/4, 12 1/2
1/2	1	1 1/8	1 1/4	1, 1 1/4, 1 1/2, 1 3/4, 2, 12 1/2
5/8	1 1/8	1 1/4	1 3/4	1, 1 1/4, 1 1/2, 1 3/4, 2, 12 1/2
3/4	1 3/8	1 3/4	1 3/4	1, 1 1/4, 1 1/2, 1 3/4, 2, 2 1/4, 2 1/2, 2 3/4, 12 1/2
7/8	1 5/8	1 3/4	2	1 1/4, 1 1/2, 1 3/4, 2, 2 1/4, 2 1/2, 2 3/4, 3, 12 1/2
1	1 3/4	2	2 1/2	1 1/4, 1 1/2, 1 3/4, 2, 2 1/4, 2 1/2, 2 3/4, 3, 4, 12 1/2

Standard Durometer: 95A Amber

### Rods

Diameters (in)	Standard Lengths (in)
1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 1, 1 1/8, 1 1/4, 1 3/8	6, 12, 24, 36, 48

Durometers: 80A, 90A, 95A

### Pads

Thickness (in)	Sizes (in)
1/4, 3/8, 7/16, 1/2, 5/8, 3/4, 7/8, 1, 1 1/4, 1 1/2, 1 3/4, 2, 2 1/2, 2 3/4, 3, 4	12x12, 20x24, 24x24 (Other Sizes Available)

Durometers: 80A, 90A, 95A

### Poly-Hammers

- Molded polyurethane head is shot-filled, with steel reinforced handle.
- Screw-in hammer faces are available in 6 color-coded durometers.
- When the hammer faces are worn out, just unscrew the face and screw-in a new face.
- 6 hammer sizes ranging from 3/4 lbs. to 7 lbs.
- Standard hammers are ORANGE.

DIECO Part #	Face #	Head Length (in)	Face Dia. (in)
PH-12	F12-*	3.3	1.4
PH-20	F20-*	3.8	1.8
PH-24	F24-*	4.0	1.9
PH-48	F48-*	5.0	2.5
PH-60	F60-*	6.0	2.9
PH-88	F88-*	7.7	2.9

\* Durometers: 60A – Clear (Soft), 70A – Blue, 80A – Green, 90A – Red, 95A – Amber, 75D – Black (Hard)

