

Anchor Lamina

Lamina Flat Products

- L-Gibs, V-Gibs, Square Gibs
- Gib Assemblies
- Guide Blocks
- Keeper Blocks
- Wear Plate
- Wear Strips

Lamina Other Products

- Stock Lifters
- Pad Retainers
- Mold Pins & Bushings
- Marsh Mellow Springs
- Hydraulics
- Cam Units
- Ball Bearing Scrub



Drill Rod

• It is used extensively in dies and punches for blanking, forming and trimming, as well as in cams, bushings, guides and gauges.

Typical applications include:

- Blanking dies • Drawing dies • Machine ways
- Cams • Forming dies • Plastic mold dies
- Coining dies • Gages • Shear Blades • Trim dies

Available in:

- AISI O-1 Oil Hardening
- AISI O-1 Metric Oil Hardening
- AISI W-1 Water Hardening
- AISI A-2 Air Hardening
- AISI A-2 Metric Air Hardening
- AISI S-7 Air Hardening
- AISI D-2 Air Hardening High Chrome

D-2 Tool Steel

- Heat treat temperature 1600-1650 F
- Quench Air or Oil
- Hardness Rockwell 60c-62c
- Applications D2 has high wear resistance, good toughness, and low distortion. It is often chosen when long tool life is required

Stocked as Premium DCF plate, flats, and rounds
Other Tool Steel Grades Available



SHOPAID
INCORPORATED

Steel Shim Stock

- Low carbon mild steel cold rolled to a #1 hard temper.
- Stiff and springy, and can be used where hardness is required.
- Can be punched or sheared with minimum burring and distortion.
- Meets the following specifications: AISI 1010 and QQS 698.

Available in .001" to .031" and in standard packages 6" x 100" or 12" x 120". Special slit widths are also available on request. Other sizes available: 6"x100", 12"x120", Assortments: 6"x25" Flat Paks, 6"x18" Flat Paks.

DIECO Part #	Description
SR2	6" x 180" .002
SR3	6" x 180" .003
SR5	6" x 180" .005
SR7	6" x 180" .007
SR10	6" x 180" .010
SR15	6" x 180" .015
SR20	6" x 180" .020
SR25	6" x 180" .025